Ocono
Italy

APDatec 105

Highly flexible PVC hose reinforced with shock resistant rigid PVC spiral



Applications	liquid manure spreading, agriculture, irrigation, waste water
Structure	soft PVC, green, transparent, plastic spiral / rigid PVC
Temperature	-25°C up to 60°C
Properties	very good flexibility, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
19	25,60	3,30	76	7,00	0,59	13,75	50	H105 019 0500 DE
25	32,00	3,50	100	7,00	0,59	18,00	50	H105 025 0500 DE
32	39,00	3,50	128	6,00	0,59	23,25	50	H105 032 0500 DE
38	45,40	3,70	152	4,00	0,59	28,00	50	H105 038 0500 DE
40	47,40	3,70	160	4,00	0,59	31,50	50	H105 040 0500 DE
45	52,40	3,70	160	4,00	0,59	33,00	50	H105 045 0500 DE
50	58,40	4,20	200	4,00	0,59	41,00	50	H105 050 0500 DE

Ocono Italy S.r.l. | Via Ca' Bassa 40 | 21100 Varese (VA) | Italy | T +39 0332 331357 | italy@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026