

VACUFLEX® VSM-EL

Very smooth internal profile hose made of electrically conductive modified TPO

Applications	industrial vacuum cleaners, vacuum cleaner, cleaning, sawing & milling, textile fiber extraction
Structure	TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix
Temperature	-50°C up to 60°C
Properties	corrugated outside, smooth inside, excellent flexibility, electrically conductive ($R \leq 10^3 \text{ Ohm}$), good flexibility restoring force after compression or bending
Norms	ATEX 2014/34/EU
Optional	The 50 mm and 60 mm inner diameters are also available in 25 m on request



Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
25	33,00	55	0,60	0,60	0,17100	30	4-4006-025-00
32	40,50	70	0,50	0,50	0,23100	30	4-4006-032-00
38	48,00	80	0,40	0,40	0,35500	30	4-4006-038-00
50	61,00	120	0,25	0,25	0,46400	30	4-4006-050-00
60	72,00	140	0,20	0,20	0,63100	30	4-4006-060-00