


VACUFLEX® PU 400 E ECO COMPRESSED

Very light weight and flexible Polyurethane hose

Applications	extraction systems, dust extraction, wood dust extraction, textile fiber extraction, air extraction
Structure	TPU / Polyester-Polyurethane, uncolored, transparent, steel wire / spring steel wire / not coated / copper plated
Temperature	-40°C up to 90°C, short term up to 125°C
Properties	light weight, very good flexibility, good abrasion resistance, good tensile strength, ultimate elongation, good ozone- & UV-resistance



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
32	36,00	0,40	36	0,60	0,30	0,14500	10	7-0500-032-16/998
51	55,00	0,40	51	0,40	0,20	0,22400	10	7-0500-051-16/998
60	64,00	0,40	60	0,40	0,20	0,26300	10	7-0500-060-16/998
70	74,00	0,40	70	0,40	0,20	0,31200	10	7-0500-070-16/998
76	80,00	0,40	76	0,40	0,20	0,33800	10	7-0500-076-16/998
80	84,00	0,40	80	0,30	0,15	0,35500	10	7-0500-080-16/998
90	94,00	0,40	90	0,30	0,15	0,40000	10	7-0500-090-16/998
100	105,00	0,40	100	0,30	0,15	0,46200	10	7-0500-100-16/998
110	115,00	0,40	110	0,20	0,10	0,50500	10	7-0500-110-16/998
115	120,00	0,40	115	0,20	0,10	0,52800	10	7-0500-115-16/998
120	125,00	0,40	120	0,20	0,10	0,55100	10	7-0500-120-16/998
125	130,00	0,40	125	0,20	0,10	0,70900	10	7-0500-125-16/998
130	135,00	0,40	130	0,20	0,10	0,73700	10	7-0500-130-16/998
140	145,00	0,40	140	0,20	0,10	0,79400	10	7-0500-140-16/998
150	155,00	0,40	150	0,20	0,10	0,85100	10	7-0500-150-16/998
160	165,00	0,40	160	0,20	0,10	0,90700	10	7-0500-160-16/998
170	175,00	0,40	170	0,10	0,05	0,96200	10	7-0500-170-16/998
175	180,00	0,40	175	0,10	0,05	0,99000	10	7-0500-175-16/998
180	185,00	0,40	180	0,10	0,05	1,01800	10	7-0500-180-16/998
200	206,00	0,40	200	0,10	0,05	1,13100	10	7-0500-200-16/998
210	216,00	0,40	210	0,10	0,05	1,18800	10	7-0500-210-16/998
220	226,00	0,40	220	0,10	0,05	1,24500	10	7-0500-220-16/998

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
225	231,00	0,40	225	0,10	0,05	1,27300	10	7-0500-225-16/998
250	256,00	0,40	250	0,05	0,02	1,41500	10	7-0500-250-16/998
275	281,00	0,40	275	0,05	0,02	1,34200	10	7-0500-275-16/998
300	306,00	0,40	300	0,05	0,02	2,53200	10	7-0500-300-16/998
325	331,00	0,40	325	0,05	0,02	1,70800	10	7-0500-325-16/998
330	336,00	0,40	330	0,05	0,02	1,73400	10	7-0500-330-16/998
350	356,00	0,40	350	0,05	0,02	1,83500	10	7-0500-350-16/998
400	406,00	0,40	400	0,10	0,02	2,09600	10	7-0500-400-16/998