Ocono
Italy

FLEXADUX® P7LPU-PAS-FOOD

Medium weight and flexible spiral hose made of Polyurethane, antistatic and food grade



Applications food production & -conveying, pharmaceutical production, extraction systems, granulate conveying, dosing

Structure Polyether-Polyurethane, transparent, steel wire / stainless steel wire

Temperature -40°C up to 100°C, short term up to 125°C

Properties good flexibility, very good abrasion resistance, permanently antistatic ($R < 10^9$ Ohm), free of halogen & softeners, very smooth inside

Norms certified according to Food EU Directive (EC) No. 1935/2004 & Regulation (EC) No. 10/2011 for E | TRGS 727, ATEX 2014/34/EU / pneumatic transport of combustible dusts (inside: zone 20, 21, 22), ATEX 2014/34/EU / use in zones 1 & 2, ATEX 2014/34/EU / use in zone 0, ATEX 2014/34/EU / aspiration (no zone or inside: zone 22) | FDA standard 21 CFR 177.2600 & 178.2010 | manufacturing process according to GMP EC 2023/2006





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
25	31,00	0,70	15	1,55	0,40	2,69	10	08100025-1000-000-00
25	31,00	0,70	15	1,55	0,40	4,03	15	08100025-1500-000-00
32	38,00	0,70	22	1,45	0,35	2,69	10	08100032-1000-000-00
32	38,00	0,70	22	1,45	0,35	4,03	15	08100032-1500-000-00
38	44,00	0,70	26	1,40	0,34	3,18	10	08100038-1000-000-00
38	44,00	0,70	26	1,40	0,34	4,77	15	08100038-1500-000-00
40	46,00	0,70	28	1,35	0,32	3,34	10	08100040-1000-000-00
40	46,00	0,70	28	1,35	0,32	5,01	15	08100040-1500-000-00
51	57,00	0,70	36	1,18	0,27	3,93	10	08100051-1000-000-00
51	57,00	0,70	36	1,18	0,27	5,89	15	08100051-1500-000-00
60	66,00	0,70	42	1,18	0,27	4,60	10	08100060-1000-000-00
60	66,00	0,70	42	1,18	0,27	6,89	15	08100060-1500-000-00
65	71,00	0,70	48	1,10	0,25	4,97	10	08100065-1000-000-00
65	71,00	0,70	48	1,10	0,25	7,45	15	08100065-1500-000-00
76	82,00	0,70	53	0,90	0,23	5,78	10	08100076-1000-000-00
76	82,00	0,70	53	0,90	0,23	8,67	15	08100076-1500-000-00
80	86,00	0,70	56	0,86	0,21	6,08	10	08100080-1000-000-00
80	86,00	0,70	56	0,86	0,21	9,12	15	08100080-1500-000-00
102	108,00	0,70	71	0,64	0,19	11,56	15	08100102-1500-000-00
102	108,00	0,70	71	0,64	0,19	7,71	10	08100102-1000-000-00
120	126,00	0,70	84	0,54	0,16	9,51	10	08100120-1000-000-00
120	126,00	0,70	84	0,54	0,16	14,26	15	08100120-1500-000-00

Ocono Italy S.r.l. | Via Ca' Bassa 40 | 21100 Varese (VA) | Italy | T +39 0332 331357 | italy@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
127	133,00	0,70	89	0,50	0,15	10,05	10	08100127-1000-000-00
127	133,00	0,70	89	0,50	0,15	15,08	15	08100127-1500-000-00
152	158,00	0,70	107	0,41	0,11	8,76	10	08100152-1000-000-00
152	158,00	0,70	107	0,41	0,11	13,14	15	08100152-1500-000-00
203	210,00	0,70	142	0,27	0,10	17,40	10	08100203-1000-000-00
203	210,00	0,70	142	0,27	0,10	26,10	15	08100203-1500-000-00
250	257,00	0,70	175	0,21	0,06	21,36	10	08100250-1000-000-00

Ocono Italy S.r.l. | Via Ca' Bassa 40 | 21100 Varese (VA) | Italy | T +39 0332 331357 | italy@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026