
Ocono
Italy

SMARTFLEX® 1.4

Medium weight and flexible spiral hose made of Polyurethane, flame retardant



Applications conveying of abrasive media, granulate conveying, industrial vacuum cleaners, wood dust extraction, conveying technology

Structure Polyether-Polyurethane, transparent, steel wire / spring steel wire / not coated / copper plated

Temperature -40°C up to 100°C, short term up to 125°C

Properties flame-retardant, permanently antistatic (R < 10^9 Ohm), hydrolysis & microbe resistant, good flexibility, very smooth inside, corrugated outside

Norms flame-retardant according to DIN 4102 / B1 | TRBS 2153/TRGS 727, ATEX 2014/34/EU / pneumatic transport of combustible dusts (inside: zone 20, 21, 22), ATEX 2014/34/EU / conveying of flammable liquids (inside: zone 0, 1, 2) | discharge capability according to BGI 739-2 with spiral earthing | DIN 26057-3





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
25	33,00	1,40	25	3,75	0,90	3,62	15	08800025-1500-000-00
25	33,00	1,40	25	3,75	0,90	2,41	10	08800025-1000-000-00
32	41,00	1,40	32	3,56	0,86	4,09	10	08800032-1000-000-00
32	41,00	1,40	32	3,56	0,86	6,13	15	08800032-1500-000-00
38	47,00	1,40	38	2,88	0,70	4,67	10	08800038-1000-000-00
38	47,00	1,40	38	2,88	0,70	7,01	15	08800038-1500-000-00
40	49,00	1,40	40	2,88	0,70	4,90	10	08800040-1000-000-00
40	49,00	1,40	40	2,88	0,70	7,35	15	08800040-1500-000-00
50	59,00	1,40	50	2,38	0,60	6,44	10	08800050-1000-000-00
50	59,00	1,40	50	2,38	0,60	9,65	15	08800050-1500-000-00
60	69,00	1,40	60	2,25	0,55	11,48	15	08800060-1500-000-00
60	69,00	1,40	60	2,25	0,55	7,65	10	08800060-1000-000-00
65	74,00	1,40	65	2,15	0,55	8,26	10	08800065-1000-000-00
65	74,00	1,40	65	2,15	0,55	12,39	15	08800065-1500-000-00
70	79,00	1,40	70	2,00	0,55	8,87	10	08800070-1000-000-00
70	79,00	1,40	70	2,00	0,55	13,30	15	08800070-1500-000-00
76	85,00	1,40	76	1,75	0,50	9,59	10	08800076-1000-000-00
76	85,00	1,40	76	1,75	0,50	14,39	15	08800076-1500-000-00
80	89,00	1,40	80	1,50	0,45	10,08	10	08800080-1000-000-00
80	89,00	1,40	80	1,50	0,45	15,12	15	08800080-1500-000-00
90	99,00	1,40	90	1,35	0,40	11,29	10	08800090-1000-000-00
90	99,00	1,40	90	1,35	0,40	16,94	15	08800090-1500-000-00

Ocono Italy S.r.l. | Via Ca' Bassa 40 | 21100 Varese (VA) | Italy | T +39 0332 331357 | italy@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
100	110,00	1,40	100	1,21	0,40	13,51	10	08800100-1000-000-00
100	110,00	1,40	100	1,21	0,40	20,26	15	08800100-1500-000-00
110	120,00	1,40	110	1,15	0,38	15,81	10	08800110-1000-000-00
110	120,00	1,40	110	1,15	0,38	23,71	15	08800110-1500-000-00
120	130,00	1,40	120	0,99	0,30	16,11	10	08800120-1000-000-00
120	130,00	1,40	120	0,99	0,30	24,16	15	08800120-1500-000-00
140	150,00	1,40	140	0,77	0,20	18,70	10	08800140-1000-000-00
140	150,00	1,40	140	0,77	0,20	28,05	15	08800140-1500-000-00
150	160,00	1,40	150	0,77	0,20	20,00	10	08800150-1000-000-00
150	160,00	1,40	150	0,77	0,20	30,00	15	08800150-1500-000-00
160	170,00	1,40	160	0,66	0,20	31,95	15	08800160-1500-000-00
160	170,00	1,40	160	0,66	0,20	21,30	10	08800160-1000-000-00
180	190,00	1,40	180	0,55	0,15	29,01	10	08800180-1000-000-00
180	190,00	1,40	180	0,55	0,15	43,52	15	08800180-1500-000-00
200	211,00	1,40	200	0,55	0,15	27,96	10	08800200-1000-000-00
200	211,00	1,40	200	0,55	0,15	41,93	15	08800200-1500-000-00
250	261,00	1,40	250	0,38	0,10	34,75	10	08800250-1000-000-00
250	261,00	1,40	250	0,38	0,10	52,12	15	08800250-1500-000-00
300	311,00	1,40	300	0,30	0,10	41,54	10	08800300-1000-000-00
350	361,00	1,40	350	0,28	0,09	23,03	5	08800350-0500-000-00
350	361,00	1,40	350	0,28	0,09	46,07	10	08800350-1000-000-00
400	411,00	1,40	400	0,25	0,09	30,41	5	08800400-0500-000-00
400	411,00	1,40	400	0,25	0,09	60,83	10	08800400-1000-000-00
450	461,00	1,40	450	0,13	0,08	34,17	5	08800450-0500-000-00
450	461,00	1,40	450	0,13	0,08	68,34	10	08800450-1000-000-00
500	511,00	1,40	500	0,10	0,07	37,92	5	08800500-0500-000-00
500	511,00	1,40	500	0,10	0,07	75,84	10	08800500-1000-000-00

Ocono Italy S.r.l. | Via Ca' Bassa 40 | 21100 Varese (VA) | Italy | T +39 0332 331357 | italy@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026