

APDatec 105

Highly flexible PVC hose reinforced with shock resistant rigid PVC spiral

Applications	liquid manure spreading, agriculture, irrigation, waste water
Structure	PVC / soft PVC, green, transparent, plastic spiral / rigid PVC
Temperature	-25°C up to 60°C
Properties	very good flexibility, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
19	25,60	3,30	76	7,00	0,59	13,75	50	H105 019 0500 DE
25	32,00	3,50	100	7,00	0,59	18,00	50	H105 025 0500 DE
32	39,00	3,50	128	6,00	0,59	23,25	50	H105 032 0500 DE
38	45,40	3,70	152	4,00	0,59	28,00	50	H105 038 0500 DE
40	47,40	3,70	160	4,00	0,59	31,50	50	H105 040 0500 DE
45	52,40	3,70	160	4,00	0,59	33,00	50	H105 045 0500 DE
50	58,40	4,20	200	4,00	0,59	41,00	50	H105 050 0500 DE