Ocono
Italy

VACUFLEX® VSM-SO2

Very smooth internal profile hose with very low flow resistance

Applications vacuum cleaner, industrial vacuum cleaners, cleaning, seed conveying, dust extraction

Structure TPO, black, opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, very good low-temperature flexibility, corrugated outside, smooth inside, crush-resistant, good flexibility restoring force after compression or bending, excellent mechanical properties, especially for higher tensile forces







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Length (m)	Article Number
25	33,00	50	0,60	0,60	0,13300	30	4-2106-025-00
32	40,50	70	0,50	0,50	0,29700	30	4-2106-032-00
38	48,00	95	0,40	0,40	0,33650	30	4-2106-038-00
40	50,00	105	0,40	0,40	0,35370	30	4-2106-040-00
50	61,00	120	0,25	0,25	0,49330	30	4-2106-050-00
60	72,00	140	0,20	0,20	0,62700	30	4-2106-060-00

Ocono Italy S.r.l. | Via Ca' Bassa 40 | 21100 Varese (VA) | Italy | T +39 0332 331357 | italy@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026